



CHANDELIER INSTALLATION INSTRUCTIONS

Installation is to be by a qualified electrician in accordance with all applicable electric codes.

1. Chandelier by TWO HILLS STUDIO. Actual shape may vary.
2. Hidden inner mounting pan attached to ceiling with appropriate fasteners. Fasteners by others.
3. Electrical junction box in ceiling by others. Turn off electricity to electrical box before installing fixture.
4. Connect black, white & ground wires from fixture to corresponding wires from junction box using appropriate wire nuts. Tuck the wires into the junction box.
5. Attach the fixture canopy to the threaded nipples of the inner mounting pan with balls or nuts provided. Secure these joints with Loctite 262 liquid threadlocker (provided) to prevent loosening of fixture due to wind or vibration.
6. Pendant sleeve with threaded pipe inside or chains provided to suspend fixture. If pendant is shipped loose from fixture, attach the threaded pipe to the coupling on top of the fixture and to the canopy with lock nuts and lock washers provided. Secure these joints with Loctite 262 liquid threadlocker (provided) to prevent loosening and rotation of fixture due to wind or vibration.
7. In most models, either the top or bottom of the fixture is open for relamping. In other cases a hinged panel is provided. Use only bulbs indicated on the fixture.
8. Fixtures are for 120 volt power supply unless labeled otherwise. Connect only to a power supply of the proper voltage.